

GEDA® SOLARLIFT



GEDA SOLARLIFT

The GEDA Solarlift gently transports highly-sensitive solar elements and photovoltaic modules quickly and safely to the roof. The specially designed solar platform ensures careful transport of the valuable modules and holds the sensitive cargo safely in place.

The GEDA Solarlift also scores when it comes to transport and storage. It can easily be transported to its deployment site as the components can be dismantled into individual pieces. Once at the construction site, the device impresses with quick and easy assembly without additional tools and the small size of the compact base unit means that it can be installed even at sites with difficult access conditions.

In addition to the single-level variants GEDA Lift 200 Standard and GEDA Lift 250 Comfort, the two-level GEDA Fixlift 250 is also available.

The load capacity in each case depends on the design of the aluminium ladder sections, the inclination and the rail length.

Technical data:



250 kg



19 m



19/38 m/min



**0.6/1.2 kW/230 V/
50 Hz/16 A**

Accessories/Load carrying devices:



Ladder section 2 m 200 kg
Art. No. 03378



Ladder section 1 m 200 kg
Art. No. 03379



Ladder section 2 m 250 kg
Art. No. 02888




Ladder section 1 m 250 kg
Art. No. 02889



Ladder prop
Art. No. 05643



General purpose platform
Art. No. 02893



Front protector for general purpose platform
Art. No. 02862



Solar platform
Art. No. 02908



Sheet carrier
Art. No. 02831




Angle track section
Art. No. 02877



Angle track section
Art. No. 02828



Wheeled undercarriage
Art. No. 02822



Roof tie
Art. No. 02826



Transport axle
Art. No. 02886



Liftbox
Art. No. 46309

**For further accessories
visit: www.geda.de**

